



Climate Action Energy Efficiency Statement

Proposed Large-scale Residential Development Planning
Application No. 1 at Flemington Lane, Balbriggan, Co. Dublin

August 2026

Waterman Moylan Consulting Engineers Limited

Block S Eastpoint Business Park, Alfie Byrne Road, Dublin D03 H3F4
www.waterman-moylan.ie

Client Name: Lagan Homes
Document Reference: Climate Action Energy Statement
Project Number: 26-079

Quality Assurance – Approval Status

This document has been prepared and checked in accordance with
Waterman Group's IMS (BS EN ISO 9001: 2015, BS EN ISO 14001: 2015)

Issue	Date	Prepared by	Checked by	Approved by
Planning	27-08-26	N. Coughlan	A. Brophy	-

Comments

Disclaimer

This report has been prepared by Waterman Moylan, with all reasonable skill, care and diligence within the terms of the Contract with the Client, incorporation of our General Terms and Condition of Business and taking account of the resources devoted to us by agreement with the Client.

We disclaim any responsibility to the Client and others in respect of any matters outside the scope of the above.

This report is confidential to the Client and we accept no responsibility of whatsoever nature to third parties to whom this report, or any part thereof, is made known. Any such party relies on the report at its own risk.

Content

1.	Introduction.....	1
2.	Building Regulations Part L 2022 Dwellings	2
2.1	Regulation 8 Part (a).....	2
2.2	Regulation 8 Part (b).....	2
2.3	Regulation 8 Part (c).....	2
2.4	Regulation 8 Parts (d & e).....	3
2.5	Regulation 8 Parts (f).....	3
2.6	Requirements for Common Areas	3
2.7	S.I No 393 of 2021 - Regulation 5 Part (f)	4
3.	Building Fabric.....	5
3.1	Elemental U-Values	5
3.2	Air Permeability	5
3.3	Thermal Bridging.....	6
4.	Heat Sources & Renewable Energy Options & Proposals	7
4.1	Air Source Heat Pumps	7
4.2	Exhaust Air Heat Pumps.....	7
5.	Climate Change Adaptation.....	8
5.1	Electric Vehicle Charging.....	8
5.2	Environmental Assessment Methodologies.....	8
5.3	Embodied Carbon	9
6.	Proposed Solutions.....	10
6.1	Residential	10

1. Introduction

Waterman Moylan Engineering Consultants have been appointed by Lagan Homes to prepare this Climate Action Energy Statement as part of the planning documentation for a proposed Large-scale Residential Development comprising 146 no. residential units at Flemington Lane, Balbriggan, Fingal, Co. Dublin.

The proposed large scale residential development (LRD) consists of 146no. dwellings in the form of 120no. houses and 26no. apartments in the following mix – 13no. 1-bed, 29no. 2-bed, 91no. 3-bed and 13no. 4-bed, and childcare facility with play space, scooter parking, car parking and drop off area on Flemington Lane. All housing will be one or two storey in height. The apartment buildings will be three storey in height. The creche will be single storey with a first storey pop up.

Three new vehicular accesses off Flemington Lane are proposed to serve the development. The proposal also provides for public open space including a Multi-Use Games Area (MUGA), communal open space associated with apartments, landscaping, boundary treatments, public lighting, car parking, motorcycle parking, bicycle parking and structures, an active travel hub and cycle route, bin storage structures, works to Flemington Lane itself including two pedestrian crossing points, 2no. ESB substations, infrastructure services and all other associated site development works.

This report identifies the energy standards with which the proposed development will have to comply and also sets out the overall strategy that will be adopted to achieve these energy efficiency targets.

The dwellings will be required to minimise overall energy use and to incorporate an adequate proportion of renewable energy in accordance with Building Regulations Part L 2022, Conservation of Energy & Fuel (hereinafter referred to as “Part L 2022 Dwellings”).

2. Building Regulations Part L 2022 Dwellings

Compliance with Building Regulations *Part L 2022 Dwellings* is broken down into six distinct categories, known as Regulation 8; parts (a) to (f).

A summary of each of these parts as listed in Technical Guidance Document L 2022 is provided below together with a description of what is required to demonstrate compliance and suggested routes to meeting the required standards.

2.1 Regulation 8 Part (a)

The regulation requires that:

Providing that the energy performance of the building is such as to limit the calculated primary energy consumption and related carbon dioxide (CO₂) to that of a nearly zero energy building within the meaning of the Directive insofar as is reasonably practicable.

Part (a) is the overarching compliance target which stipulates the required overall reduction in energy consumption and carbon emissions for new dwellings.

This requires that the energy consumption and carbon emissions of every dwelling is assessed using the DEAP software and that reductions of 70% in energy consumption and 65% in carbon emissions are achieved. The baseline against which this reduction is to be measured is considered to be a dwelling which is constructed to perfectly comply with the 2005 version of Building Regulations Part L.

The ratio of the energy consumed by the proposed dwelling to a similar dwelling constructed to 2005 energy efficiency standards is referred to as the “Energy Performance Co-efficient”

2.2 Regulation 8 Part (b)

The regulation requires that:

Providing that, the nearly zero or very low amount of energy required is covered to a very significant extent by energy from renewable sources, including energy from renewable sources produced on-site or nearby;

This requires that all new dwellings are provided with a renewable energy source. The regulations state that 20% of the total energy consumed within the dwelling must be provided from renewable thermal sources (solar thermal, biomass, heat pumps) or renewable electrical sources (Photovoltaic, Micro-wind).

In practical terms, for a multiple unit development, this requirement is usually met by incorporating PV panels at roof level, incorporating air source heat pump technology or by adding an element of biomass or micro-Combined Heat & Power (CHP) to a district heating scheme.

Where CHP is included, the renewable energy is considered to be the waste heat which is generated as a by-product of the electricity produced. Specific calculation methods are set out within TGD *Part L 2022 Dwellings* which detail how compliance should be demonstrated.

2.3 Regulation 8 Part (c)

The regulation requires that:

Limiting heat loss and, where appropriate, availing of heat gain through the fabric of the building;

This requires that the fabric of the building is designed to minimise heat loss from the building and that the air permeability of the structure limits the unwanted passage of air into the building.

Typical compliant U-Values are as follows.

Pitched roof	0.16 W/m ² K
Flat roof	0.20 W/m ² K
Walls	0.18 W/m ² K
Floor	0.18 W/m ² K
Windows	1.4 W/m ² K

The u-values of individual elements can be relaxed if required provided that compensatory measures are taken on other elements and that the overall area weighted u-value for the entire dwelling is the same as it would have been if all individual elements had complied.

The thermal bridging details of junctions in the envelope of the building (floor-wall; wall-window; wall-roof, etc) must also be designed and constructed in accordance with the guidance set out in Limiting Thermal Bridging and Air Infiltration – Acceptable Construction Details

Every dwelling must also be subjected to an air pressure test to determine the air tightness. All dwellings must achieve an air tightness of less than 5m³/m²/hour when tested at 50 Pascals. In multiple dwelling developments with repeating apartment types, testing can be conducted on a representative sample of units in accordance with Table 1.5.4.3 of TGD *Part L 2022 Dwellings*.

2.4 Regulation 8 Parts (d & e)

The regulation requires that:

Providing and commissioning energy efficient space and water heating systems with efficient heat sources and effective controls;

Providing that all oil and gas fired boilers shall meet a minimum seasonal efficiency of 90%;

These require that gas or oil-fired boilers are at least 90% efficient and that heating controls allow independent time control of the heating (2 zones for dwellings larger than 100m²) and hot water. Heating in each zone should also be controlled by room thermostats (in the case of heating) and cylinder stats (in the case of hot water).

2.5 Regulation 8 Parts (f)

The regulation requires that:

Providing to the dwelling owner sufficient information about the building, the fixed building services and their maintenance requirements so that the building can be operated in such a manner as to use no more fuel and energy than is reasonable.

This requires that information is provided to the dwelling owner which relates to the effective and efficient operation of the systems installed in that dwelling. Instructions on how to control the heating & hot water systems based on time and temperature requirements.

2.6 Requirements for Common Areas

Section 0.1.2.3 requires that:

Where a new dwelling forms part of a larger building, the guidance in this document applies to the individual dwelling, and the relevant guidance in Technical Guidance Document L - Conservation of Fuel and Energy – Buildings other than dwellings applies to the non-dwelling parts of the building

2.7 S.I No 393 of 2021 - Regulation 5 Part (f)

The regulation requires that:

(a) A multi-unit building containing one, or more than one, dwelling that is new shall have installed ducting infrastructure (consisting of conduits for electrical cables) for each car parking space, to enable the subsequent installation of recharging points for electric vehicles where the parking space is:

(i) located inside the building concerned, or

(ii) is within the curtilage of the building concerned.

(c) A new building that is a dwelling, other than where the dwelling forms part of a multi-unit building, where a parking space is located within the curtilage of the dwelling, shall have installed appropriate electric vehicle recharging infrastructure to enable the subsequent installation of recharging points for electric vehicles.

This requires that ducting provision for the future installation of car charging point be made in all carparks with more than 10 parking spaces associated with multi-unit residential buildings. It also requires that individual / own-door dwellings which have on curtilage parking are provided with ducting infrastructure to allow the future installation of e-car charging.

3. Building Fabric

Before considering efficient building services or renewable energy systems, the form and fabric of a building must be assessed and optimised so as to reduce the energy demand for heating, lighting and ventilation. Target performance levels have been identified by the design team and are presented below.

3.1 Elemental U-Values

The U-Value of a building element is a measure of the amount of heat energy that will pass through the constituent element of the building envelope. Increasing the insulation levels in each element will reduce the heat lost during the heating season and this in turn will reduce the consumption of fuel and the associated carbon emissions and operating costs.

It is the intention of the design team to exceed the requirements of the building regulations. Target U-Values are identified below.

U-Values	Range of Target Values Proposed	Part L 2022 (Dwellings) Compliant Values
Floor	0.10 to 0.18 W/m ² K	0.18W/m ² K
Roof (Flat)	0.12 to 0.20 W/m ² K	0.20 W/m ² K
Roof (Pitched)	0.10 to 0.16 W/m ² K	0.16 W/m ² K
Walls	0.10 to 0.18 W/m ² K	0.18 W/m ² K
Windows	0.9 to 1.4 W/m ² K	1.4W/m ² K

3.2 Air Permeability

A major consideration in reducing the heat losses in a building is the air infiltration. This essentially relates to the ingress of cold outdoor air into the building and the corresponding displacement of the heated internal air. This incoming cold air must be heated if comfort conditions are to be maintained. In a traditionally constructed building, infiltration can account for 30 to 40 percent of the total heat loss, however construction standards continue to improve in this area.

With good design and strict on-site control of building techniques, infiltration losses can be significantly reduced, resulting in equivalent savings in energy consumption, emissions and running costs.

In order to ensure that a sufficient level of air tightness is achieved, air permeability testing will be specified in tender documents, with the responsibility being placed on the main contractor to carry out testing and achieve the targets identified in the tender documents.

A design air permeability target of **3 m³/m²/hr** has been identified for the houses on the site.

The air permeability testing will be carried out in accordance with BS EN 13829:2001 'Determination of air permeability of buildings, fan pressurisation method' and CIBSE TM23: 2000 'Testing buildings for air leakage'

3.3 Thermal Bridging

Thermal bridges occur at junctions between planar elements of the building fabric and are typically defined as areas where heat can escape the building fabric due to a lack of continuity of the insulation in the adjoin elements.

Careful design and detailing of the manner in which insulation is installed at these junctions can reduce the rate at which the heat escapes. Standard good practice details are available and are known as Acceptable Construction Details (ACDs). Adherence to these details is known to reduce the rate at which heat is lost.

The rate at which heat is lost is quantified by the Thermal Bridging Factor of the dwelling and measured in W/m^2K . The Thermal Bridging Factor is used in the overall dwelling Part L calculation, this value can be entered in three different ways:

0.15W/m ² K	Used where the ACDs are not adhered to
0.08W/m ² K	Used where the ACDs are fully adhered to
< 0.08 W/m ² K	Used where the thermal details are thermally modelled and considered to perform better than the ACDs

It is intended that the ACDs will be adhered where suitable benchmarks exist and/or that thermal modelling will be carried out for any non-standard junction details within proposed development.

4. Heat Sources & Renewable Energy Options & Proposals

All new dwellings must meet overall energy performance levels (as defined by the Energy Performance Coefficient - EPC) and must have a portion of their annual energy demand provided by renewable energy sources.

The renewable energy source can be thermal energy such as solar thermal collection, biomass boilers or heat pumps or it can be electrical energy as generated by photovoltaic solar panels or wind turbines. The minimum renewable energy contributions defined in Part L 2022 Part (b) is 20% of the total energy consumption for the dwelling.

The options presented below set out the options for the dwellings proposed for the site. The final selection and combination of technologies will most likely be selected from these options based on a more in-depth technical and financial appraisal of the technologies which will be carried out during detailed design.

4.1 Air Source Heat Pumps

Air source heat pumps (ASHPs) utilise grid supplied electricity to extract thermal energy from a heat source, in this case, the external ambient air. While the electricity consumed is obviously not renewable energy, the efficiency at which a heat pump operates allows a significant portion of the heat delivered to be considered as renewable energy. The amount of heat considered to be renewable is determined by the efficiency of the heat pump and the “primary energy conversion factor” for grid supplied electricity. Typically, approximately 40% to 50% of the heat supplied is considered to be renewable energy.

Air source heat pumps require an indoor and an outdoor component. The outdoor unit is the evaporator which extracts the thermal energy from the ambient air while the indoor unit typically includes the heating buffer tanks and the hot water cylinder for the dwelling. The outdoor unit is typically located in the back garden of a dwelling.

In recent years, the design of ASHPs has improved bringing about higher efficiencies and reduced costs. This, in turn, has led to an increase use of this technology in large scale housing developments. Certified seasonal efficiencies of some models can exceed 500% meaning that the use of this technology can easily deliver compliance with current Part L requirements.

4.2 Exhaust Air Heat Pumps

Exhaust Air heat pumps (EAHPs) operate in a very similar manner to the more conventional air source heat pumps and utilise grid supplied electricity to extract thermal energy from a heat source, in this case, the internal air within the apartment. The internal air is extracted from kitchens and wet rooms and is drawn into the heat pump via ductwork in the ceiling void. The heat pump extracts heat from this air before expelling it from the apartment.

As noted in Section 4.2 above, the electricity consumed is not renewable energy but the efficiency at which a heat pump operates allows a significant portion of the heat delivered to the dwelling be considered as renewable.

There are a number of manufacturers offering products of this type and the certified seasonal efficiencies of some models can exceed 450% in heating mode and 170% to 190% in hot water mode. These efficiencies can deliver Part L 2022 compliance in most circumstances but in some instances may need supplementary PV panels in order to meet the required energy targets.

There is no requirement for a separate Mechanical Extract Ventilation (MEV) systems when an exhaust air heat pump is used as the heat pump draws the air from all wet rooms in the same manner as an MEV system would. The fan will run continuously to ensure that the minimum ventilation rates are maintained and the supply air to the dwelling is provided through trickle vents in each habitable room.

5. Climate Change Adaptation

5.1 Electric Vehicle Charging

In accordance with the Fingal Development Plan, the design for the site will seek to encouraging the use of public transport by using the principles of environmental assessment methodologies to reduce the reliance on cars and encourage a shift to less carbon intensive modes of transport. This approach is more fully dealt with the in the mobility / transportation reports submitted with the application.

In addition, measures will also be put in place to ensure the site provides adequate infrastructure of electric vehicles. All in-curtilage parking spaces will be capable of being fitted with EV charging points while all off-curtilage spaces will be ducted to facilitate the future installation of EV charging in all spaces, with 20% of spaces being provided with active vehicle charging facilities.

5.2 Environmental Assessment Methodologies

Addressing operational energy use in a manner set out in the preceding sections of this report is a vital component of any construction project however consideration must also be given to other aspects of sustainable design such as water use, material selection and minimising pollutants.

Various assessment methodologies have been developed by organisations such as the Building Research Establishment (BREEAM Methodology) and the US Green Building Council (LEED Certification) to measure the performance of various environmental and sustainable aspects of the design, construction and operation of proposed developments.

The Irish Green Building Council has also developed a similar assessment methodology in recent years which is specifically aimed at residential developments in Ireland. **The Housing Performance Index (HPI)** assessment provides a method for measuring the performance of residential developments against a range of verifiable indicators that are divided into five technical categories

- Environment,
- Economic,
- Health and Wellbeing,
- Quality Assurance
- Sustainable Location.

It allows several levels of achievement based on good, better and best practice. The award of the certificate is based on the overall attainment across all categories.

A decision will be made during detailed design as to whether formal HPI certification will be sought on the project, however, the principles set out within the HPI system will be used as guidance throughout the design process regardless of whether certification is targeted.

5.3 Embodied Carbon

Recent advances in the energy efficiency of buildings have reduced operational energy use to such an extent that the life cycle carbon emissions of a building are actually influenced more by the carbon that is embodied in the materials and processes used during the construction than it is by the carbon emitted as a result of energy used in the buildings operation. As such, the embodied carbon of a building must now be considered if a construction project is to be considered low carbon or “net-zero” carbon.

Addressing the embodied carbon requires that all the key building element categories (substructure, structure, façade, MEP services) are assessed to identify the optimal solutions in terms of embodied carbon and assess them through a multidisciplinary and holistic approach, considering implications in different areas such as efficiency, cost, programme etc.

The process of design and of material and product selection must include an analysis of the final embodied carbon and comparison with benchmarks to identify the areas that need to be optimised. This process allows the building designers and procurement managers to focus on how to eliminate the impact of the key identified hotspots, through comparative assessments and specification of products that demonstrate low embodied carbon and facilitate the production of the final embodied carbon assessment at the end of the detailed design to identify the expected impact of the Development.

6. Proposed Solutions

The preceding sections of this report set out the regulatory requirements with which the scheme will have to comply while identifying a number of technologies and design approaches that may be utilised to achieve compliance.

The building fabric standards and the technology solutions discussed will all be assessed in greater detail during the detailed design stage of the project. A cost benefit analysis of all these available solutions will be carried out to determine the correct balance between an efficient building envelope and the most appropriate combination of technology and renewable energy systems.

The proposed approach to achieving Part L Compliance will be based on a combination of the solutions below once a detailed analysis has been completed at detailed design stage. A final decision will be made once capital costs, renewable targets and regulation compliance have all been compared to find the most appropriate solution.

6.1 Residential

The most likely overall solution that will be implemented will include the following measures

- Meet or exceed minimum U-Value standards
- Achieve a high level of air tightness (typically $3\text{m}^3/\text{m}^2/\text{hr}$)
- Ensure thermal bridging details are designed to meet the performance of the ACDs or an equivalent standard.
- Provide an appropriate combination of technologies to ensure energy consumption is in line with Part L 2022 requirements. This will either include air source heat pumps and/or an alternative heating system such as gas boilers with PV panels for renewable energy.
- Install centralised mechanical ventilation systems to ensure adequate ventilation rates are achieved in the dwelling which maximising the benefits of the airtight construction

UK and Ireland Office Locations



